

**IN THE CLAIMS:**

Please amend Claims 1, 6, 7, 8, 9 11 and 14 and cancel Claims 4, 5 and 10 as follows:

1. (Currently Amended) A modulation/ demodulation method for ~~multi-amplitude~~  
~~digital~~ quadrature amplitude modulated (QAM) signals with non-equidistant phases transmitted  
via an orthogonal frequency division multiplexing (OFDM) communication system characterized  
in that the amplitude of said signals are separately and coherently processed, whereas the phases  
of respectively subsequent symbols on a same subcarrier are differentially modulated and  
demodulated, respectively.

2. (Original) The method of claim 1, characterized in that said amplitudes are coherently  
transmitted and are corrected in the receiver.

Al  
cont  
3. (Original) The method of claim 2, characterized in that at the demodulation stage the  
amplitude distortions of said multi-amplitude digital modulated signals due to frequency  
selectivity of the respective channel are separately corrected on each subcarrier.

4. (Canceled).

5. (Canceled).

6. (Currently Amended) ~~The method of claim 4, characterized in that~~ A modulation/  
demodulation method for quadrature amplitude modulated (QAM) signals with non-equidistant  
phases transmitted via an orthogonal frequency division multiplexing (OFDM) communication  
system characterized in that the amplitude of said signals are separately and coherently

processed, whereas the phases of respectively subsequent symbols on a same subcarrier are differentially modulated and demodulated, respectively;

wherein the correction factors for the subcarrier amplitudes of said QAM symbols are computed from quadrature phase shift keying (QPSK) signals combined in one respective frame of a plurality of QFDM symbols comprising a defined number of QAM data symbols and a defined number of QPSK control signals.

7. (Currently Amended) The method according to ~~claim 4~~ claim 1, characterized in that sixteen QAM symbols are adopted as said QAM signals.

Cl  
Cont

8. (Currently Amended) ~~The method of claim 7, characterized in that~~ A modulation/ demodulation method for quadrature amplitude modulated (QAM) signals composed of sixteen QAM symbols with non-equidistant phases transmitted via an orthogonal frequency division multiplexing (OFDM) communication system characterized in that the amplitude of said signals are separately and coherently processed, whereas the phases of respectively subsequent symbols on a same subcarrier are differentially modulated and demodulated, respectively;

wherein for amplitude correction of the receiver, a running mean of the correction factor is performed over a defined time window.

9. (Currently Amended) ~~The method of claim 4, characterized in that~~ A modulation/ demodulation method for quadrature amplitude modulated (QAM) signals composed of sixteen QAM symbols with non-equidistant phases transmitted via an orthogonal frequency division multiplexing (OFDM) communication system characterized in that the amplitude of said signals

are separately and coherently processed, whereas the phases of respectively subsequent symbols on a same subcarrier are differentially modulated and demodulated, respectively;

wherein a frame structure is adopted comprising n QPSK symbols followed by m 16 QAM symbols.

10. (Canceled)

11. (Currently Amended) ~~The OFDM system of claim 10, characterized in that~~  
An orthogonal frequency division multiplexing (OFDM) system for transmission of a multi-amplitude digital modulated signal from a transmitter to a receiver via a radio channel, wherein,

*Q*  
*Cont*  
- on the transmitter side, phase differential encoder means (5) are provided for differentially modulating subsequent symbols on the same subcarrier,

- on the receiver side, differential phase decoding means (21) are provided for demodulating said respectively subsequent symbols on said same subcarrier, and in that

- means are provided on said both sides for coherent processing of the amplitudes of said signals;

said transmitter is adapted to process a coded data stream with a block frame structure consisting in each frame of a sequence of n quadrature phase shift keyed (QPSK) control symbols followed by m sixteen quadrature amplitude modulated (16 QAM) data symbols and comprising:

- a demultiplexer means (1) for separating said control symbols and said data symbols, and

- for feeding said control signals to QPSK modulator means (2) for mapping of two bits each into QPSK complex symbols and for supplying said data symbols to a 16 QAM modulator means (3) for mapping of four bits each into 16 QAM complex symbols,

- first multiplexing means (4) for multiplexing said QPSK complex symbols and said 16 QAM complex symbols and for supplying the resulting data stream to

- a phase differential encoder means (5) for differential modulation of the phases of respectively subsequent symbols on a same subcarrier and keeping the respective amplitudes of said symbols unchanged,

- second multiplexing means (7) for transferring the resulting data symbol stream into OFDM signals that are subject to an inverse fast Fourier transformation (8) to produce a baseband OFDM-modulated signal,

- quadrature modulator means (10) for modulating said baseband signal with carriers having 90° phase difference and supplying the thus modulated signal to

- D/A-converter means (11) followed by an up-converter means (11) to hook the analog D/A-converter output signal to a given carrier frequency for transmission.

12. (Original) The OFDM system of claim 11, characterized in that null symbol generating means (6) are provided for setting unused subcarriers leaving said phase differential encoder means (5) at the band edges to zero.

13. (Previously Presented) The OFDM system of claim 11, characterized in that for reducing multipath interference effects a guard interval inserting means (9) is provided for

inserting before each symbol a copy of a defined number of the last samples of the inverse fast Fourier transformed time domain OFDM symbols.

14. (Currently Amended) ~~The OFDM system of claim 10, characterized in that~~  
An orthogonal frequency division multiplexing (OFDM) system for transmission of a  
multi-amplitude digital modulated signal from a transmitter to a receiver via a radio channel,  
wherein,

- on the transmitter side, phase differential encoder means (5) are provided for  
differentially modulating subsequent symbols on the same subcarrier,

- on the receiver side, differential phase decoding means (21) are provided for  
demodulating said respectively subsequent symbols on said same subcarrier, and in that

- means are provided on said both sides for coherent processing of the amplitudes of said  
signals;

said receiver is adapted to receive, process and demodulate said radio channel transmitted signal and comprising:

- a down-converter means (14) for converting the received signal from said carrier frequency down to an intermediate frequency;

- analogue-to-digital converter means for digitizing said intermediate frequency signal;

- a quadrature demodulator means (16) for detecting and generating a baseband signal from said A/D-converted intermediate frequency;

- a time synchronizing means (17) for generating a window for fast Fourier transformation indicating the effective symbol portion of the OFDM signal;

- a fast discrete Fourier transformation means (18) for producing complex frequency domain symbols of said effective symbol portion of the OFDM signal;
- first demultiplexer means (19) for demultiplexing the FFT transformed OFDM signal into useful data and for canceling unused subcarriers at the band edges;
- phase differential decoder means (21) for demodulating the phases of subsequent symbols on the same subcarrier with simultaneous coherent processing of the amplitudes;
- second demultiplexer means (22) for separating QPSK symbols and QAM symbols;
- QPSK demodulator means (26) for demapping of said QPSK complex symbols into corresponding bits;
- QAM demodulator means (27) for demapping of said QAM complex symbols into corresponding bits; and
- third multiplexing means (28) for multiplexing of said demodulated QPSK bits and said demodulated QAM bits according to the adopted frame structure.

15. (Original) The OFDM system of claim 14, characterized in that the QPSK complex symbols output from said second demultiplexer means (22), on the one hand, are sent via hardlimiter means (23) to said QPSK demodulator means (26) and, on the other hand are sent to an amplitude distortion determining mean for generating a running means of the respective QPSK signal, and in that the QAM complex symbols output by said second demultiplexer means (22) is supplied to an amplitude correction means (25) for amplitude correction according to the respective running means of amplitude before supplying the amplitude corrected QAM complex symbols to said QAM demodulator means (27).